



ROBINIA RB1243







+

10 kids

17,4 m²





Material specification

- ullet Construction made of Robinia very durable acacia wood with a diameter of \sim 18 cm without sharp edges, resistant to weather conditions,
- Platforms made of Robinia very durable acacia wood, resistant to weather conditions,
- Side panels made of Robinia very durable acacia wood without sharp edges, resistant to weather conditions
- Rubber door with textile reinforcement,
- Moving elements made of durable HPL plate, resistant to weather conditions,
- Telescope made of stainless steel and durable HDPE plate, resistant to weather conditions,
- Dashboard and steering wheel made of durable HDPE plate, resistant to weather conditions,
- Steel ropes in polypropylene braid, connected with durable plastic elements, stainless steel or aluminum,
- Calibrated stainless steel chains, preventing fingers entrapment,
- Screws covered with plastic caps and/or stainless steel screws,



Facilitating disability



easy access



integration



Intellectual development



manipulation



siah




Physical development





rest











Product technical sheet

ROBINIA RB1243

Product data

Length	161 cm	
Width	120 cm	
Total height	129 cm	
Age group	1+ years	
Number of users	10 kids	
Safety zone	17,4 m2	
Free fall height	<60 cm	
The height of the platforms	25 cm	
In accordance with norm EN	1176-1:2017	
Weight of the heaviest part	37 kg	
Dimensions of the largest part	160x18x18 cm	
Availability of spare parts	YES	
Installation time	2,0 h	

Data is subject to change without prior notice.

Additional information

- equipment adapted for the disabled; intended for public playgrounds;
- equipment has a certificate issued by an accredited entity or a declaration of conformity;
- no sharp edges or chinks that would pose a danger of jimming the head, fingers or any other body parts;
- anchoring on flat surface, 80/70/60 cm deep;
- render is for reference only, the actual appearance of the equipment and its color may vary;

Guarantee



30 year guarantee -Structural strength of steel and stainless steel components



15 year guarantee -Structural failure of steel and stainless steel, for dynamic equipment



10 year guarantee - Structural failure of high density polyethylene and high pressure laminates components



5 year guarantee - Corrosion of stainless steel and hot dip galvanized and powder coated components; against bark beetles and rot in case of wooden structural elements

Detailed information in the guarantee card



VAT: 534-250-14-46 PHONE: +48 42 203 24 99 ext. 26

M: +48 793 404 991





Surfaces according to EN 1176-1:2017

	Description (mm)	Layer thickness (cm)	Maximum fall heights (cm)
Turf/ top layer of soil (A,B,C)	-	-	≤100
hark (A.C.)	Particle size from 20 to 80 40	30	≤200
bark (A,C)		40	≤300
woodchips (A,C)	Particle size from 5 to 30	30	≤200
		40	≤300
sand or gravel (A,C)	Particle size from 0,25 to 8	30	≤200
		40	≤300
synthetic attested (A,B,C)	Tested according to EN 1177		60

Product technical sheet

ROBINIA RB1243

Amount of safe surface corresponding with free fall height:

HIC <60 17,4 m²

Data is subject to change without prior notice.

