

## ROBINIA RB1313



5+



5 kids



35,6 m<sup>2</sup>

### Material specification

- Construction made of Robinia - very durable acacia wood with a diameter of ~ 18 cm without sharp edges, resistant to weather conditions,
- Platforms made of Robinia - very durable acacia wood, resistant to weather conditions,
- Side panels made of Robinia - very durable acacia wood without sharp edges, resistant to weather conditions
- Slides made of stainless steel,
- Steel ropes in polypropylene braid, connected with durable plastic elements, stainless steel or aluminum,
- Calibrated stainless steel chains, preventing fingers entrapment,
- Handles made of steel rope in polypropylene braid,
- Screws covered with plastic caps and/or stainless steel screws,



### Physical development



balance



community



sliding



climbing





**1**  
number of  
towers



**1**  
number of  
slides



**3**  
number of activity  
elements

## Product technical sheet

# ROBINIA RB1313


## Product data

|                                |                     |
|--------------------------------|---------------------|
| Length                         | 510 cm              |
| Width                          | 310 cm              |
| Total height                   | 345 cm              |
| Age group                      | 5+ years            |
| Number of users                | 5 kids              |
| Safety zone                    | 35,6 m <sup>2</sup> |
| Free fall height               | 165 cm              |
| The height of the platforms    | 150 cm              |
| slide platform height          | 150 cm              |
| In accordance with norm EN     | 1176-1:2017+A1:2023 |
| Weight of the heaviest part    | 97 kg               |
| Dimensions of the largest part | 420x18x18 cm        |
| Availability of spare parts    | YES                 |
| Installation time              | 6 h                 |


Data is subject to change without prior notice.

## Additional information

- equipment intended for public playgrounds;
- equipment has a certificate issued by an accredited entity or a declaration of conformity;
- no sharp edges or chinks that would pose a danger of jamming the head, fingers or any other body parts;
- anchoring on flat surface, 80/70 cm deep;
- slide should not be installed southwards;
- render is for reference only, the actual appearance of the equipment and its color may vary;



35,6 m<sup>2</sup>



## Guarantee

**30**

30 year guarantee - Durability of steel and stainless steel structural elements

**15**

15 year guarantee - Durability of steel and stainless steel structures of mobile devices; durability of Robinia wood structural elements

**10**

10 year guarantee - Structural strength of HDPE, 100% recycled HDPE and HPL elements; structural elements made of 100% recycled material (composite)

**5**

5 year guarantee - Corrosion resistance of stainless steel and hot-dip galvanized and powder-coated steel elements, resistance to bark beetles and rotting of wooden structural elements

Detailed information in the guarantee card

**Vinci Group Sp. z o.o.**  
Seminaryjna 9 Street  
99-400 Łowicz

VAT: 534-250-14-46  
PHONE: +48 42 203 24 99 ext. 26  
M: +48 793 404 991



biuro@vinci-play.com  
info@vinci-play.com  
[www.vinci-play.com](http://www.vinci-play.com)

## Surfaces according to EN 1176-1:2017+A1:2023

|                                 | Description (mm)             | Layer thickness (cm) | Maximum fall heights (cm) |
|---------------------------------|------------------------------|----------------------|---------------------------|
| Turf/ top layer of soil (A,B,C) | -                            | -                    | ≤100                      |
| bark (A,C)                      | Particle size from 20 to 80  | 30                   | ≤200                      |
|                                 |                              | 40                   | ≤300                      |
| woodchips (A,C)                 | Particle size from 5 to 30   | 30                   | ≤200                      |
|                                 |                              | 40                   | ≤300                      |
| sand or gravel (A,C)            | Particle size from 0,25 to 8 | 30                   | ≤200                      |
|                                 |                              | 40                   | ≤300                      |
| synthetic attested (A,B,C)      | Tested according to EN 1177  |                      | 165                       |

## Product technical sheet

# ROBINIA RB1313

### Amount of safe surface corresponding with free fall height:

HIC 100 6,0 m<sup>2</sup>

HIC 115 2,6 m<sup>2</sup>

HIC 150 8,4 m<sup>2</sup>

HIC 165 18,6 m<sup>2</sup>

Data is subject to change without prior notice.

