

Product technical sheet

SWING ST0521





Material specification

- Hot-dip galvanized and powder coated or powder galvanized and powder coated construction of 100 x 100 mm profile,
- Hot-dip galvanized and powder coated or powder galvanized and powder coated or stainless steel construction elements,
- Steel ropes in polypropylene braid, connected with durable plastic elements, stainless steel or aluminum,
- Certified, durable polypropylene rope 140 x 140 mm,
- Calibrated stainless steel chains, preventing fingers entrapment,
- Stainless steel swing fittings,
- Stainless steel screws and/or screws covered with plastic caps,
- Safe end caps on top of the structure made of rubber or polypropylene,




22/07/2022


VAT: 534-265-18-84 PHONE: +48 42 203 24 99 ext. 26 M: +48 793 404 991




biuro@vinci-play.com info@vinci-play.com www.vinci-play.com










Guarantee



30 year guarantee -Durability of steel and stainless steel structural elements



10 year guarantee - Structural strength of HDPE, 100% recycled HDPE and HPL elements; structural elements made of 100% recycled material (composite)

Product technical sheet SWING ST0521

Product data

Length	490 cm
Width	310 cm
Total height	270 cm
Age group	3 - 14 years
Number of users	4 kids
Safety zone	13,5 m2
Free fall height	130 cm
In accordance with norm EN	1176-1:2017+A1:2023
Weight of the heaviest part	31 kg
Dimensions of the largest part	352x10x10 cm
Availability of spare parts	YES
Installation time	3 h
Color options	

Data is subject to change without prior notice.

Additional information

- equipment intended for public playgrounds;
- equipment has a certificate issued by an accredited entity or a declaration of conformity;
- no sharp edges or chinks that would pose a danger of jamming the head, fingers or any other body parts;
- anchoring on flat surface, 80/70 cm deep;

5

 render is for reference only, the actual appearance of the equipment and its color may vary;

> 5 year guarantee - Corrosion resistance of stainless steel and hot-dip galvanized and powder-coated steel elements, resistance to bark beetles and rotting of wooden structural elements

Detailed information in the guarantee card

Vinci Sp. z o.o. Seminaryjna 9 Street 99-400 Łowicz VAT: 534-265-18-84 PHONE: +48 42 203 24 99 ext. 26 M: +48 793 404 991



biuro@vinci-play.com info@vinci-play.com www.vinci-play.com

2/3



Surfaces according to EN 1176-1:2017+A1:2023


	Description (mm)	Layer thickness (cm)	Maximum fall heights (cm)
Turf/ top layer of soil (A,B,C)	-	-	≤100
bark (A,C)	Particle size from 20	30	≤200
	to 80	40	≤300
weedebine (A.C)	Particle size from 5	30	≤200
woodchips (A,C)	to 30	40	≤300
cond or gravel (A C)	Particle size from	30	≤200
sand or gravel (A,C)	0,25 to 8	40	≤300
synthetic attested (A,B,C)	Tested according	to EN 1177	130


Product technical sheet SWING ST0521

Amount of safe surface corresponding with free fall height:

|--|

Data is subject to change without prior notice.





Vinci Sp. z o.o. Seminaryjna 9 Street 99-400 Łowicz VAT: 534-265-18-84 PHONE: +48 42 203 24 99 ext. 26 M: +48 793 404 991



biuro@vinci-play.com info@vinci-play.com www.vinci-play.com